

Flat Panel Monitor

MODEL 171KM Multi-scan

17" Industrial LCD Openframe Display – Multi-scan Signals

Features

- High Brightness & Long Life TFT Panel
- Resolution (1280 x 1024 pixels)
- Metal Cased Construction
- Console/Rack Mounting – 1 U Rack (21mm)
- 12Vdc or 115/230Vac Power Inputs
- Touchscreens - Easily integrated



Specifications

- | | | | |
|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| • Type: | A-Si Color TFT | • Horizontal Scan | Multi scan 15.80KHz signals |
| • Colors: | 16.2 M | • Vertical Scan: | Multi scan 45-90 Hz signals |
| • Resolution: | 1280 x 1024 pixels (native) | • AC Model: | 115/230V 50/60Hz |
| • Active Area: | 338 x 270 mm | | External AC/DC Power Pack |
| • Backlight Life: | 50,000 hours typical | • Power Consumption: | 54 W (max) |
| • Brightness: | 300 cd/m2 typical (nits) | • Dimensions: | 360 x 298 x 21 mm (approx) |
| • Contrast Ratio: | 700:1 | • Weight: | 4.5 Kg (approx) |
| • Viewing Angles: | 75/75/75/60 | • Housing: | Zinc-plated steel |
| • Response Time: | 8 msec (tr + tf) | • Operating Temp: | 0 to 50 °C (32 to 122 °F) |
| • Video Connections: | Analog RGB & TTL (optional) | • Storage Temp: | -20 to 60 °C (-4 to 140 °F) |
| • Input Connectors: | 15-pin HD, 9 Pin (optional) | • Approvals: | UL certified |
| • Sync. Type/Level: | Separate H&V (+/-ve) TTL | | |